



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx LCIE 15.0037X issue No.: 0 Certificate history:

Status: **Current**

Date of Issue: **2015-07-22** Page 1 of 3

Applicant: **HRLM Technology Incorporated Company**
No. 15, West Henggang Street
Yangcheng Lake Town, Xiangcheng District, Suzhou, Jiangsu
China

Electrical Apparatus: **Explosion-proof floodlight, Type: BFD610-****
Optional accessory:

Type of Protection: **Ex d, Ex tb**

Marking: **Ex d IIB+H2 T... or ...°C Gb**
Ex tb IIIC T...°C Db

(see attachment for full marking)

Approved for issue on behalf of the IECEx
Certification Body:

Julien GAUTHIER

Position:

Certification Officer

Signature:
(for printed version)

Date:

2015-07-22

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the **Official IECEx Website**.

Certificate issued by:

Laboratoire Central des Industries Electriques (LCIE)
33 Avenue du General Leclerc
FR-92260 Fontenay-aux-Roses
France

Documents relative to LCIE certification activities (Certificates, QARs, ExTRs) can be registered under the references "LCI" or "LCIE".





IECEx Certificate of Conformity

Certificate No.: IECEx LCIE 15.0037X

Date of Issue: 2015-07-22

Issue No.: 0

Page 2 of 3

Manufacturer: **HRLM Technology Incorporated Company**
No. 15, West Henggang Street
Yangcheng Lake Town, Xiangcheng District, Suzhou, Jiangsu
China

Additional Manufacturing location
(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2011 Edition: 6.0	Explosive atmospheres - Part 0: General requirements
IEC 60079-1 : 2007-04 Edition: 6	Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
IEC 60079-31 : 2008 Edition: 1	Explosive atmospheres – Part 31: Equipment dust ignition protection by enclosure "t"

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:
FR/LCIE/ExTR15.0057/00

Quality Assessment Report:

FR/LCIE/QAR14.0010/00



IECEx Certificate of Conformity

Certificate No.: IECEx LCIE 15.0037X

Date of Issue: 2015-07-22

Issue No.: 0

Page 3 of 3

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The BFD610-** explosion-proof floodlight consists of an aluminum alloy enclosure, a cemented toughened glass light transmitting cover and two entries. The enclosure is divided into two compartments as follows:

- the electrical compartment includes terminals, ballast, a capacitor, a trigger (for high pressure sodium lamp or metal halide lamp) and two entries for external connection. The two entries are closed by two blanking elements before packaging.
- the lighting compartment includes a lamp holder and a bulb.

The wire-through part between these two compartments is encapsulated.

See attachment for type designation and specific parameters of the concerned protection mode.

Routine test:

Each apparatus shall be submitted to a static overpressure test under 1.2 MPa during minimum 10 seconds in accordance with clause 16.1 of IEC 60079-1:2007 standard.

CONDITIONS OF CERTIFICATION: YES as shown below:

- Operating ambient temperature: -20°C to +55°C.
- Repair of the threaded joints must be made in compliance with the structural specifications provided by the manufacturer. Repair must not be made on the basis of values specified in Table 3 or Table 4 of IEC 60079-1:2007 standard.
- The entries shall be equipped with Ex certified cable glands with compatible modes of protection for the intended use.
- In order to ensure the temperature class the apparatus shall be mounted at horizontal or vertical downward position.




Annex 01 to Certificate IECEx LCIE 15.0037X issue 00



1. General product information:

Type designation:



2. Marking:

HRLM Technology Incorporated Company

Address: ...

Type: BFD610-** (1)

Serial number: Year of construction:

Ex d IIB+H₂ T... or ...°C Gb (2)

Ex tb IIIC T...°C Db (2)

IECEx LCIE 15.0037X

WARNING – AFTER DE-ENERGIZING, DELAY 15 MINUTES BEFORE OPENING

WARNING – POTENTIAL ELECTROSTATIC CHARGING HAZARD – SEE INSTRUCTIONS

WARNING – DO NOT OPEN WHEN ENERGIZED

CAUTION – USE FASTENERS WITH YIELD STRESS $\geq 450 \text{ N/mm}^2$

(1): completed by type designation

(2): completed by temperature classes specified in ratings.

3. Ratings:

1) Rated voltage: 220 V ~ 240 V AC 50/60 Hz

2) Light source parameters:

Lamp type	Lamp specification	Ballast	Trigger	Compensation capacitor
High Pressure Mercury	HPL-N 250 W	BHLA 250L	/	CP18BU28 18 μ F
	HPL-N 400W	BHLA 400L	/	CP25BU28 25 μ F
High Pressure Sodium	SON 150W	BSN 150L	SN58(T5)	CP18BU28 18 μ F
	SON 250W	BSN 250L	SN58(T5)	CP32ET28 32 μ F
	SON 400W	BSN 400L	SN58(T5)	CA32GV28 50 μ F
Metal Halide	MH UPS 175W	BPI 175L	SI53	CP12BP28 12 μ F
	HPI PLUS 250W BU	BSN 250L 200TS	SI51	CP18BU28 18 μ F
	MH UPS 400W	BPI 400L	SN53	CP25CU28 25 μ F

3) Temperature classes:

Lamp type	Rated power (W)	Temperature class			
		-20°C \leq Ta \leq +40°C		-20°C \leq Ta \leq +55°C	
		Gas	Dust	Gas	Dust
Metal Halide	175	T4	T130°C	T3	T195°C
	250	T3	T190°C	T3	T195°C
	400	T3	T190°C	T3	T195°C
High Pressure Mercury	250	T3	T190°C	T3	T195°C
	400	T3	T190°C	208°C	T200°C
High Pressure Sodium	150	T4	T130°C	T3	T195°C
	250	T3	T190°C	T3	T195°C
	400	T3	T195°C	218°C	T210°C